



LEVASSEUR
Your paint expert

EASY COLOR GOLD 90I COPPER 903 SILVER 905

PRODUCT DESCRIPTION

Metallic paint - Gold, copper or silver aspect.

APPLICATION

Outdoors - Indoors, can be applied on wood derivatives, plasters, metallic surfaces and non-ferrous metals properly prepared.

Apply the appropriate primer before coating with Easy Color Gold, Copper or Silver.

To avoid oxydation and enhance outdoor resistance apply a top coat of Varnish (Polyfond 2KPU or acryl varnish waterbased).

TECHNICAL SPECIFICATIONS

Binder : 100% acrylic resins in solutions.

Pigment : Bronze or aluminium powder.

Solvents : Aromatic hydrocarbons.

Dry extract : Gold/Copper : Weight : 44,3% ± 2 – Volume : 22,6% ± 2.

Silver : Weight : 28,9% ± 2 – Volume : 18,8% ± 2.

Density : Gold/Copper : 1,210 kg/l (±0,05 at 20°C).

Silver : 0,980 kg/l (±0,05 at 20°C).

Flash point : 25°C.

Thickness dry film : 10µ on an average.

Coverage : ± 10-12 m²/l.

Drying : 10 to 30 minutes at 23°C and 50% HR.

Recoatible : 24 hours.

Aspect : Semi-gloss metallic.

USE OF THE PRODUCT

Mix carefully before use.

Brush and roll : Ready to use.

Spray : 5 to 20% Thinner 05/317bis.

Cleaning : Thinner 05/317bis

It is recommended to wear safety goggles and spray mask.

STORAGE CONDITIONS

Conservation : 4 years from production date.

Keep in a closed container in a dry, cool and well ventilated area at a temperature between + 5 and + 35°C.

Our information on the technical product is used only as assistance to professional workers. During the implementation of our products, we always advise to start with a test on a small area.

S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL
Tel. 02/ 376 00 18 – Fax. 02/ 376 38 86 – info@g-levasseur.com – www.levasseur.be