



**LEVASSEUR**  
*Your paint expert*

# EASYTOP

## PRODUCT DESCRIPTION

Tinted transparent multicoat wood decorative product, fungicide and water repellent.

## PROPERTIES

Fungicide.  
UV resistant.  
Water repellent.  
Humidity controller properties.  
Scratch proof.  
Durable and weather resistant.  
Easy to apply.  
Does not drip.  
Highly decorative.

## APPLICATION

Outdoor-indoor.  
Long-life protection.  
Application on new wood and as a renovation coat on old clean, dry and transparent surfaces  
Supports : Indigenous and tropical woods, already impregnated woods.  
Chalets, doors, windows frames, balustrades, facade coatings, timber woods, fences, boardings, shutters,...

## SURFACE PREPARATION

New surfaces:  
Polish, dust and degrease with a solvent agent (use of ammonia for afzelia wood)  
On impregnated wood : 3 coats of Easytop.  
On non-impregnated wood : 1 coat of Eeasytop 501 + 2 coats of Easytop.  
Repainting :  
Remove all slightly adhering parts.  
Clean with white spirit or wash if required.  
Polish if the surface is still glossy, dust, touch up any bare parts.  
Subsequently apply 2-3 coats of Easytop.

## CLEANING OF MATERIAL

White spirit.

---

### S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL  
Tel. 02/ 376 00 18 - Fax. 02/ 376 38 86 - [info@g-levasseur.com](mailto:info@g-levasseur.com) - [www.levasseur.be](http://www.levasseur.be)



**LEVASSEUR**  
*Your paint expert*

## CARACTERISTIQUES

Composition : Binder : Alkyd urethane resins  
Pigment : Micronised, not opacifying and solid light.  
Solvents : Active fungicide.  
Dry content : Weight : 45% +- 2. Volume : 37% +- 2.  
Density : 0,90 kg/L à 20°C (depending on shade).  
Flash point : 41°C according to DIN 51.758.  
Application : Brush or roller (ready to use), spray (dilution with +- 10% white spirit).  
Aspect : Semi-gloss.  
Thickness dry film : 20µ on average.  
Coverage : 15-20 m<sup>2</sup>/L.

## DRYING

4-5 hours depending on the absorption capacity of the wood.  
Recoatable : 24 heures.

## STORAGE CONDITIONS

2 years in closed sealed cans. Stock in a ventilated area with temperature between 5°C and 30°C.

*Our information on the technical product is used only as assistance to professional workers. During the implementation of our products, we always advise to start with a test on a small area.*

---

### S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL  
Tel. 02/ 376 00 18 – Fax. 02/ 376 38 86 – [info@g-levasseur.com](mailto:info@g-levasseur.com) – [www.levasseur.be](http://www.levasseur.be)