



LEVASSEUR
Your paint expert

EVERETHANE SATIN

PRODUCT DESCRIPTION

Varnish in solvent phase, thixotropic, anti UV, pine oil enriched, for finishing outdoor and indoor woodwork. Satin appearance. Highly transparent pigmentation. Comes colourless and in 13 wood and deco shades. Application by brush or long bristle roller (special varnish).

APPLICATION AREA

Wooden window frames in native or exotic timber, exterior doors, gates, verandas.
All indoor woodwork: furniture, panelling, beams, etc.

PREPARATION OF THE SURFACE TO BE TREATED

- All products for outdoor woodwork are to be reserved for the treatment of vertical or oblique surfaces (angle > 15°).
- All the edges must be rounded to a curvature radius of at least 2.5 mm.
- The pigmented products have the advantage of excellent resistance to damage caused by UV rays. The colourless is to be reserved for indoor use only.

For new wood: sand and dust correctly before the first coat of Everethane Satin slightly diluted (or preferably Everethane Mat). Then apply two coats of Everethane Satin. Sand between each coat for a finer and longer lasting look.

For varnished wood in good condition: lightly sand and carefully clean the surface to be treated before applying one or two coats of Everethane Satin.

On greyed wood, or on a coating in bad condition: scraping and sand down to the "white" wood and proceed like on new wood.

The moisture content of the wood must be less than 16%.

APPLICATION

By brush.

Never use the colourless alone outdoors. All coloured varnishes can be mixed with each other (stir beforehand to liquefy the varnish before mixing).

The final colour can vary depending on the wood species and the treatment applied (always do a test beforehand).

CLEANING OF EQUIPMENT

White spirit or thinner Eversolvant

CHARACTERISTICS

Binding agents: Modified alkyd resin.

Solvent: Aliphatic.

Appearance: Satin

Colours: See colour chart

Viscosity: Thixotropic.

Dry extract by volume: Approx. 45% (colourless)

Density: 0.90 +/- 0.05

Yield: 10 to 12 m²/L per coat, depending on the species and preparation of supports.

S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL
Tel. 02/ 376 00 18 - Fax. 02/ 376 38 86 - info@g-levasseur.com - www.levasseur.be



LEVASSEUR
Your paint expert

PROPERTIES

Enhances the veining of wood by its highly transparent pigmentation.

Excellent resistance to U.V. and bad weather.

Ideal for the decoration and finishing of fine outdoor woodwork. Everethane Satin guarantees the dimensional stability of wooden parts.

The high running point makes a product very pleasant to apply.

DRYING CONDITIONS

For optimal drying, the woodwork should be placed in a well-ventilated place. If necessary, make the air flow to eliminate solvents and accelerate the drying process.

Never expose the woodwork to direct sunlight or too close to a source of heat.

DRYING TIME AT 60% RH AND 20°C

Touch-dry: 4 hours

Manipulable: 8 hours

Time between coats: 24 hours

STORAGE CONDITIONS

1 year in original, closed, and unopened packaging.

Store in a well-ventilated, dry area at a temperature between +5 and +30°C.

Our product guidelines and application technical recommendations are provided to support professional users. We recommend performing a test sample before application.

S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL
Tel. 02/ 376 00 18 - Fax. 02/ 376 38 86 - info@g-levasseur.com - www.levasseur.be