



LEVASSEUR
Your paint expert

EVERXYL PLANT OIL

PRODUCT DESCRIPTION

Transparent plant oil which contains more than 60% of bio-sourced materials is a product that protects the interior wood from humidity and tannin extraction while allowing wood to keep its natural look.

APPLICATION AREA

All types of clean and dry wood: Furniture, panelling, doors, all other interior joinery

PREPARATION OF THE SURFACE TO BE TREATED

Apply directly on raw wood. Sand if the wood is already covered with a varnish to expose the natural wood. Please note that the product will not revive wood that is gray or in poor condition.

APPLICATION

Ready-to-use product to be applied to raw wood with a brush. Apply 2 coats for more chemical resistance.

CLEANING OF EQUIPMENT

Water

CHARACTERISTICS

Appearance of the dry film: Matt
Dry extract by weight: 34% +/- 1%
Density: 1,05
Viscosity at 20°C: 300cp +/- 100cp
Theoretical yield: 12m²/L

PROPERTIES

Enhances colourless, matt. Blocks tannin extraction through contact with water.
Resistant to water, coffee, wine, ketchup and oil stains, does not leave marks or streaks.

DRYING TIME AT 60% RH AND 20°C

Re-apply after 4 hours for a 2nd coat to obtain better resistance. Dry after 24 hours.

STORAGE CONDITIONS

1 year in original, closed, and unopened packaging.
Store in a well-ventilated, dry area at a temperature between +5 and +30°C.

Our product guidelines and application technical recommendations are provided to support professional users. We recommend performing a test sample before application.

S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL
Tel. 02/ 376 00 18 - Fax. 02/ 376 38 86 - info@g-levasseur.com - www.levasseur.be