



**LEVASSEUR**  
*Your paint expert*

# TEAK OIL

## PRODUCT DESCRIPTION

Teak Oil is a nutrishng oil for teak. It's designed to protect facilitate cleaning of treated surfaces.

## APPLICATION

Impregnation product for exotic woods.  
Use on strong woods, indoor and outdoor.

## PRECAUTIONS

The temperature of the substrate should be kept between 5°C and 35° C.

## SURFACE PREPARATION

Be sure that the wood to treat is perfectly clean and dry.

## APPLICATION

Shake well before use. Apply one coat of Teak Oil with a cloth or a brush.  
Let the oil dry according to surface dry time. If necessary apply a second coat of Teak Oil.

## CLEANING OF MATERIAL

With White-Spirit right after use.

## DRYING TIME AT 60% HR and 20°C

Free of dust : 8 hours.  
Complete : After 24 hours.

## STORAGE CONDITIONS

Keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition.  
Containers must be kept tightly closed.

*Our information on the technical product is used only as assistance to professional workers. During the implementation of our products, we always advise to start with a test on a small area.*

---

### S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL  
Tel. 02/ 376 00 18 - Fax. 02/ 376 38 86 - [info@g-levasseur.com](mailto:info@g-levasseur.com) - [www.levasseur.be](http://www.levasseur.be)