



LEVASSEUR
Your paint expert

LAQUE RS

PRODUCT DESCRIPTION

Thixotropic consistency satin enamel.
Can be applied on all surfaces: wood, metals, plaster, etc.
RS Lacquer provides excellent coverage and a smooth finish.

FEATURES

Microporous, moisture-regulating, and stabilizing.
Resistant to substrate deformation.
Durable and flexible.
Washable and brushable.

SURFACE PREPARATION

Surfaces should be prepared with a coat of Flexaprim FO, lightly sanded after drying.

Woodwork:

- For new wood: light sanding and dusting (exotic woods should be degreased)
- For painted wood: sanding and degreasing or stripping

As a primer: dilute with 5–10% White Spirit

As an intermediate coat or finish: use as is

Other materials: treat like standard lacquer with an appropriate undercoat.

APPLICATION INSTRUCTIONS

Laque RS can be applied with a brush, roller, or spray gun. A slight dilution can be done with White Spirit.
For spraying, whether high or low pressure, add 15% White Spirit.

TECHNICAL SPECIFICATIONS

Coverage: 10 to 12 m ² /liter	Resine type : Alkyd-uréthane
Appearance of dry film : sation	Solid content (by weight) : 67%
Density : 1.26	Flash point : 40°C
Touch dry : 5 à 6 heures	Recoatable : 24heures
VOC: < 300 g/l (EU limit values for this product (cat. IIA/d): 300 g/l (2010))	

CLEANING AND THINNING

White Spirit

Our product information and technical recommendations are intended to assist professional workers. During application, we always advise starting with a test.

S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL
Tel. 02/ 376 00 18 – Fax. 02/ 376 38 86 – info@g-levasseur.com – www.levasseur.be