



LEVASSEUR
Your paint expert

PRIM'ISOL

PRODUCT DESCRIPTION

Insulating matte primer and finish for interiors. It can also be used as an exterior primer.

Prim'Isol is used as a universal primer on white wood, exotic wood, plaster, render, cement, MDF, coated plasterboard, plywood, chipboard, render, old alkyd paints, etc.

Prim'Isol blocks nicotine and moisture stains and has been specially designed to optimally and effectively block the tannins of special woods (merb, affzelia, cedar, etc.). Color: White

COMPOSITION

Water-based alkyd emulsion, without cosolvent.

INSTRUCTIONS FOR USE

This product can be diluted with 5 to 8% water for the first coat. For the second (finishing) coat, it should be used neat.

Air-assisted airless application: Optimal performance with 5% water dilution, using a 415-421 and 515-521 nozzle, and pressure between 120 and 220 bar (GRACO FINISHPRO 395-225V EUR VISION Airless and Air-Assisted).

DRYING

Recovery after 4 hours

CLEANING THE EQUIPMENT

In the water.

PROPERTIES

Solids content: 60%

Density: 1.59

Coverage: 8–10 m²/ltr depending on the substrate.

VOC: The EU limit values for this product (Cat. IIA/a) are 75g/l (2007) and 30g/l (2010); the current value is 2g/l.

STORAGE CONDITIONS

Fears frost.

Our information on the technical product is used only as assistance to professional workers. During the implementation of our products, we always advise to start with a test on a small area.

S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL
Tel. 02/ 376 00 18 - Fax. 02/ 376 38 86 - info@g-levasseur.com - www.levasseur.be