



**LEVASSEUR**  
*Your paint expert*

# PRIMER ONE

## PRODUCT DESCRIPTION

Primer One is a white matt paint, based on acrylic styrene copolymer resin, used indoors as a primer on walls and ceilings.

Improves coverage, reduces brightness differences and neutralizes surface porosity.

## APPLICATION FIELD

Primer One is used as a universal primer on plaster, ceiling, cement, brick, old paint, coatings, concrete, roughcast, gyproc, coated plasterboard.

## SURFACE PREPARATION

New surfaces: Surfaces must be degreased, dust-free and dry. Fix the absorbent or flaking surfaces.

Old surfaces: Remove any adherent or flaky elements. Repair the surface with a suitable coating, sand and dust.

At the end of the preparatory works, surface aspect should be similar to the new one.

## PROPERTIES

Viscosity: 4000cp      Dry extract: 60%  
Density: 1,54          VOC: <1 g/l.  
Coverage: 10-12 m<sup>2</sup>/L according to surface porosity

## APPLICATION

Brush / rol: Can be diluted with 1 to 3% of water

Spray gun: Airless :Ready to use – Low pressure: Dilution with at least 10-20% of water.

## DRYING TIME

Dust free: 15-30 minutes    -    Recoatable: 2 hours

## CLEANING OF THE MATERIAL

With water.

## STORAGE CONDITIONS

1 year in the original closed packaging. Store in a well ventilated area at a room temperature between + 5 and + 35°C. Not resistant to frost.

*Our information on the technical product is used only as assistance to professional workers. During the implementation of our products, we always advise to start with a test on a small area.*

### S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL  
Tel. 02/ 376 00 18 - Fax. 02/ 376 38 86 - [info@g-levasseur.com](mailto:info@g-levasseur.com) - [www.levasseur.be](http://www.levasseur.be)