



LEVASSEUR
Your paint expert

WOOD PRIMER

PRODUCT DESCRIPTION

Wood Primer is a water-based acrylic primer specifically designed for application on interior and exterior woodwork.

The product is applied in 1 coat before applying a covering finish.

Appearance: Matt white

PREPARATION OF THE SUBSTRATE TO BE TREATED

The wood must be sanded and then dusted off before applying the product.

Most wood species are suitable, but it is recommended to conduct a preliminary test.

CONDITIONS OF USE

Ambient temperature: Min. 10°C

Humidity: Max. 80%

Substrate temperature: Min. 10°C

APPLICATION

Wood Primer can be applied with a brush, roller, or spray gun.

If necessary, the product can be diluted with 5 to 10% water.

To avoid adhesion problems (such as contamination), we recommend applying the finishing coat within 5 days.

CARACTÉRISTIQUES

Resin: Acrylic resins

Density: 1.53 g/cm³

Dry content: 66% by weight – 48% by volume

VOC: <20g/L

Theoretical coverage: 10m²/L

DRYING TIME (20°C ET 65% HR)

Dust dry: 5 minutes

Touch dry: 15 minutes

Recoat time: 5 hours

CLEANING OF EQUIPMENT

With water.

S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL
Tel. 02/ 376 00 18 – Fax. 02/ 376 38 86 – info@g-levasseur.com – www.levasseur.be



LEVASSEUR
Your paint expert

STORAGE CONDITIONS

Storage: 1 year in the original, sealed, and unopened container. Store in a ventilated area at a temperature between +5°C and +35°C.
Sensitive to freezing.

Our product information and technical recommendations are intended to assist professional users. When applying, we always recommend starting with a test.

S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL
Tel. 02/ 376 00 18 – Fax. 02/ 376 38 86 – info@g-levasseur.com – www.levasseur.be