

EASY COLOR DECO PEARL

PRODUCT DESCRIPTION

Pearl coloured waterbased clear coat (High gloss)

Gloss level: 87% Rhopoint: 60°.

PROPERTIES

Very resistant to water and mechanical wear.

Very good weather resistant outside

Support has to be prepared according the DIN 18363 Teil c norm.

Apply 2 layers of clear coat respecting I2h waiting time between the layers to obtain a maximum result.

SUBSTRATES

Can be applied over any waterbased or solvent based paint.

If you need to apply this clear coat over an epoxy or PU paint a drying time of more then 72h has to be respect.

In this case the surface has to be sand (P400) before application for a better adhesion.

Can also be applied on painted or unpainted glassfiber wallpaper, concrete, plaster, wooden panels

APPLICATION

Application: Brush roller and spray gun.

Dilution: 2% when applied with brush or roller, 5-10% with spray gun.

For spray gun:
Nossle: 1,3 à 1,6 mm
Pressure: 1.5 à 2.5 bar
Apply 40 microns dry
Viscosity: 30 to 40 sec.
DIN 4 mm / 20°C

PROPERTIES

Density: 0.93 Kg/L

Viscosity: 1200cp (Haake rotor $n^{\circ}I - 22^{\circ}C$)

Drying: 2 hours

Consumption: 8-10m²/L according to the substrate

VOC: 60g/L

CLEANING

Water.

1



STORAGE CONDITIONS

I year in closed sealed cans. Stock in a ventilated area with temperature between 5°C and 30°C.

Our information on the technical product is used only as assistance to professional workers. During the implementation of our products, we always advise to start with a test on a small area.