



**LEVASSEUR**  
*Your paint expert*

# EASY COLOR DECO PLATINUM 915

## PRODUCT DESCRIPTION

Water borne paint for wall application – Platinum effect.

## PROPERTIES

Water borne product : odorless, free using, no plastifier, no cosolvent.  
Good opacity.  
Regular penetration on substrate.  
Regular drying.  
Easy to clean.  
Good washability.

## APPLICATION

Support must be clean and properly prepared as mentioned in DIN 18363 Teil c.

### **New ground :**

At least 28 days of drying for plaster and concrete.

- Take off grease, dust and clean well.
- Repair cracks with appropriate coating.
- Treat metal parts with a primer.
- Tannic wood needs to be treated with isolated primer.
- Chalky surface needs to be treated with a fixator primer.

### **Old ground :**

After preparation : same as new ground.

- Take off all non-adherent parts. If a washing is done with high pressure, support has to be totally dry.
- Chalky surface needs to be treated with a fixator primer.

## APPLICATION ENVIRONMENT

Temperature has to be between 10°C and 30°C.  
Higher temperature could have a significant influence on drying time.  
Humidity level <80 %.

## SURFACE PREPARATION

New walls or painted walls, clean and without any chalky problem.

- Direct application : Walls, ceilings, plaster, gypsum boards, cement, wall paper.
- After support preparation : wood, compressed wood, metal ferrous and non ferrous.

---

### **S.A. LEVASSEUR NEWCO N.V.**

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL  
Tel. 02/ 376 00 18 – Fax. 02/ 376 38 86 – [info@g-levasseur.com](mailto:info@g-levasseur.com) – [www.levasseur.be](http://www.levasseur.be)



**LEVASSEUR**  
*Your paint expert*

## CARACTERISTIQUES

Composition : Binder : Aqueous polymer.  
Aspect : Thixotropic.  
Application : Low pressure gunspray or airless.  
Coverage : 8-11 m<sup>2</sup>/L on clean support without any loss.

## CLEANING OF MATERIAL

Water.

## DRYING TIME (20°C AND 60% HR)

Touch free : 1 hour.  
Recoatable : 4 hours.

## STORAGE CONDITIONS

1 year in closed sealed cans.  
Stock in a ventilated area with temperature between 5°C and 30°C.

*Our information on the technical product is used only as assistance to professional workers. During the implementation of our products, we always advise to start with a test on a small area.*

---

### S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL  
Tel. 02/ 376 00 18 – Fax. 02/ 376 38 86 – [info@g-levasseur.com](mailto:info@g-levasseur.com) – [www.levasseur.be](http://www.levasseur.be)