



LEVASSEUR
Your paint expert

DECAP BIO LIQUID

PRODUCT DESCRIPTION

Liquid stripper formulated for industrial stripping in baths.
Product based on biodegradable, flammable, non-harmful, non-irritating and pH-neutral solvents.

APPLICATION FIELD

Indoors - Outdoors.
All types of paint on various surfaces (wood, metal, etc.)
For delicate surfaces, carry out a preliminary test and let act less long.
Silicates, lime and whitewash must be removed using other methods.

USE OF THE PRODUCT

Immerse the surface to be stripped in the stripping bath and leave to air (between 10 and 90 minutes at a temperature above 10°C).
A higher temperature will speed up the process.
Remove the waste using a scraper or abrasive sponge (fine abrasive).
Decap Bio Liquid does not damage the surface (wood, metal, etc.) and does not require rinsing.
After light sanding (if necessary), it is possible to repaint very quickly afterwards.
If the surface allows it, and if additional cleaning is necessary, high-pressure cleaning can be carried out after stripping.
During application, avoid contact with flames (cigarettes, lighters, blowtorches, angle grinders, welders, heat guns, electrical cables, etc.). Indoors, the room must be well ventilated.

PROPERTIES

Density: 1 +/- 0.01
pH: 7 +/- 0.02
Health and safety: It is always advisable to wear protective clothing, gloves and safety goggles. Indoors, the room must be well ventilated. Cover the stripping bath.

STORAGE CONDITIONS

1 year in a tightly closed container in a dry, cool and well ventilated area with a temperature between + 5°C and + 35°C.

Our information on the technical product is used only as assistance to professional workers. During the use of our products, we always advise to start with a test on a small area.

S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL
Tel. 02/ 376 00 18 - Fax. 02/ 376 38 86 - info@g-levasseur.com - www.levasseur.be