



# Technical data sheet

PROTECTION MADE EASY

---

## Solvatane

---

### Description and destination of the product

---

**Solvatane** is the standard thinner for one and two component polyurethanes.

**Solvatane** is composed of different anhydrous solvents. The combination has good solvent properties for polyurethanes which form a film by chemical reaction.

### Type of binder

---

Acetats and aromatic hydrocarbons.

### Technical data

---

○ **Density:** 0.9 (± 0.03) g/cm<sup>3</sup>

### Use

---

**Solvatane** is recommended ad thinner and cleaning solvent for the following paint systems :

- ***Polyzinc, Polysilco, Polymicace, Polytar*** and ***Monoseal***,
- ***Polygloss***
- ***Mixtane***
- ***Cryltane AC*** and ***Cryltane CF***
- ***Polyfloor***
- ***Polyroof Thix***
- ***Sprayfiller***
- ***VHM, HM, VHK, VHA, VHI, HK***-qualities

### Storage stability

---

Minimum 2 years in the original, unopened packing in a closed environment at temperatures between -40°C and +50°C.

## Safety measure

---

For detailed information about safety measures, personal protection and transport data of this product, we refer to the safety data sheet.

*The last update of our technical data sheets is always available at our website: [www.libertpaints.be](http://www.libertpaints.be)*

### **Disclaimer**

*The information given in this technical data sheet is only a general product description, based on our experiences and tests and therefore does not represent a specific practical case. Consequently Libert Paints doesn't guarantee the functionality or result and takes no responsibility in this respect.*

*We advise our clients to test the applicability of the product to the nature and the state of the surfaces and to carry out the necessary representative tests in case of doubt. Please contact our R&D department as the occasion arises.*

*Attention: our clients should verify whether the present technical data sheet hasn't been replaced by a more recent version.*