

SURFACER AGUA

PRODUCT DESCRIPTION

Surfacer Agua is a sprayable industrial filler based on acrylic resin emulsion, with high coverage, good surface hardness, and a VOC \leq 80 g / L. Colours: White (other colours available on demand).

APPLICATION FIELD

The product can be used as a primer and wood filler.

PRODUCT REFERENCE

D3/126

TERMS OF USE

Room temperature : Min. 10°C. Humidity level : Max. 80% HR. Temperature of the substrate : Min. 10°C

APPLICATION

Application with brush or rol: Ready to use For spray application:

- Add 10% water
- Opening 1.8 to 2.0 mm
- Pressure 2.5 to 3.5 bar
- For Airmix application:
- Ready to use
- Opening 0.23 to 0.28 mm
- Product pressure 60 to 100 bar
- Air pressure 3.0 to 4.0 bar
- For Airless application:
- Opening 0.23 to 0.28 mm
- Product pressure 100 to 150 bar

CLEANING OF THE MATERIAL

With water.



CARACTERISTICS

Viscosity: 45 sec DIN 4 at 20°C.

DRYING TIME AT 60% HR AND 20°C

Off dust : 40 minutes Out of touch : 60 minutes Recoatable : After 2h30 Sandable : After 2h30 Drying can be accelerated by providing good ventilation or by heating to a maximum of 60°C.

STORAGE CONDITIONS

Conservation: 6 months in a tightly closed container and refrigerated. Not resistant to frost, do not transport or store below 5°C.

Our information on the technical product is used only as assistance to professional workers. During the implementation of our products, we always advise to start with a test on a small area.