



# Technical data sheet

PROTECTION MADE EASY

---

## Thinner 1

---

### Description and destination of the product

---

**Thinner 1** is a thinner which is, thanks to its slow evaporation, very suitable for brush applications. At high ambient temperatures or extreme air movements (for example wind or outdoor applications on pylons) an acceptable flow out and de-aeration is however possible by using **Thinner 1**.

### Type of binder

---

Aromatic hydrocarbons.

### Technical data

---

 **Density:** 0.87 ( $\pm$  0.03) g/cm<sup>3</sup>

### Use

---

**Thinner 1** is recommended to be used with the following paint systems :

- quick drying alkyd paints (for example **Mecavit**, **Mecavit Satin** and **Primavit**)
- one or two component polyurethanes (for example **Polysilco** or **Cryltane AC**)
- vinylcopolymers (for example **Durozinc**)

### Storage stability

---

Minimum 2 years in the original, unopened packing in a closed environment at a temperature between -40°C and +50°C.

### Packaging

---

1, 5 and 25 litres

## Safety measure

---

For detailed information about safety measures, personal protection and transport data of this product, we refer to the safety data sheet.

*The last update of our technical data sheets is always available at our website: [www.libertpaints.be](http://www.libertpaints.be)*

### **Disclaimer**

*The information given in this technical data sheet is only a general product description, based on our experiences and tests and therefore does not represent a specific practical case. Consequently Libert Paints doesn't guarantee the functionality or result and takes no responsibility in this respect.*

*We advise our clients to test the applicability of the product to the nature and the state of the surfaces and to carry out the necessary representative tests in case of doubt. Please contact our R&D department as the occasion arises.*

*Attention: our clients should verify whether the present technical data sheet hasn't been replaced by a more recent version.*